

Model Number 097	<b>4 CONDUCTOR TWISTED SHIELDED CABLE</b>			Revision: NR ECN #:						
<b>Performance</b> Number of Conductors Cable Style Cable Configuration <b>Environmental</b> Temperature Range <b>Electrical</b> Capacitance (conductor to conductor @ 70 °F (21 °C)) <b>Physical</b> Cable Jacket Diameter Cable Jacket Material Cable Jacket Color Conductor Style Conductor Material Conductor Diameter (26 AWG) Shield Type Over Conductor(s) Shield Material Over Conductor(s) Filler Material Bend Radius (minimum) Weight <i>All specifications are at room temperature unless otherwise specified.            In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.	<b>ENGLISH</b> 4 Multi Conductor - Shielded Twisted Bundle -58 to +250 °F 27.5 pF/ft 0.170 in Polyurethane Black Stranded - 19 Strands 38 AWG Tin Plated Copper 0.040 in Braid: 94% Minimum Coverage Tinned Copper Synthetic FFP 1.70 in 0.338 oz/ft	<b>SI</b> 4 Multi Conductor - Shielded Twisted Bundle -50 to +121 °C 90.2 pF/m 4.318 mm Polyurethane Black Stranded - 19 Strands 38 AWG Tin Plated Copper 1.016 mm Braid: 94% Minimum Coverage Tinned Copper Synthetic FFP 43.18 mm 31.463 gm/m	<b>OPTIONAL VERSIONS</b> Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	<b>NOTES:</b> [1] Typical.						
					<table border="1"> <tr> <td data-bbox="1331 542 1457 607">Entered: <i>JH</i></td> <td data-bbox="1457 542 1583 607">Engineer: <i>DMP</i></td> <td data-bbox="1583 542 1709 607">Sales: <i>MFG</i></td> <td data-bbox="1709 542 1835 607">Approved: <i>MD</i></td> <td data-bbox="1835 542 1942 607">Spec Number:</td> </tr> <tr> <td data-bbox="1331 607 1457 639">Date: <i>11/3/05</i></td> <td data-bbox="1457 607 1583 639">Date: <i>11/3/05</i></td> <td data-bbox="1583 607 1709 639">Date: <i>11/3/05</i></td> <td data-bbox="1709 607 1835 639">Date: <i>11/3/05</i></td> <td data-bbox="1835 607 1942 639">32186</td> </tr> </table>	Entered: <i>JH</i>	Engineer: <i>DMP</i>	Sales: <i>MFG</i>	Approved: <i>MD</i>	Spec Number:
Entered: <i>JH</i>	Engineer: <i>DMP</i>	Sales: <i>MFG</i>	Approved: <i>MD</i>	Spec Number:						
Date: <i>11/3/05</i>	Date: <i>11/3/05</i>	Date: <i>11/3/05</i>	Date: <i>11/3/05</i>	32186						
				<b>IMI SENSORS</b> 3425 Walden Depew, NY 14043 Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com						