




VEHICLE & POWERTRAIN NVH SENSORS

 **PCB PIEZOTRONICS**
AN AMPHENOL COMPANY

 **ENDEVCO**
AN AMPHENOL COMPANY

pcb.com | endevco.com



NVH - NOISE, VIBRATION & HARSHNESS

NVH stands for noise, vibration, and harshness and is an industry term associated with the treatment of vibration and audible sounds. Noise denotes unwanted sound; and hence the need to negate these sounds and vibrations. Vibrations above and below a specific range may not be detectable to the human ear, but may still require treatments for improved product performance and longevity. The frequency of the noise is paramount, as it dictates which method of treatment or what material will work best. Harshness usually refers to treatments of transient frequencies or shock.

NVH refinement has become an essential vehicle development attribute, as it is directly related to legal compliance, product quality, driving pleasure, brand image, and most importantly customer satisfaction.

Advanced NVH test methods and analytical simulation tools are prerequisites in today's fast paced automotive market to ensure front-end optimization of new designs for sound and vibration performance while still maintaining a balance with fuel efficiency, drivability, and component durability.

CONCEPT DEVELOPMENT

The concept stage of the vehicle development process not only determines the most fundamental architecture of the automotive structure, but also offers an opportunity to reduce the amount of downstream development effort needed to achieve performance and attribute targets by optimizing core structures and system configurations and striking a balance between fuel economy, emissions, performance, ride, and NVH.

Typical NVH activities could include:

- Structural computer aided engineering (CAE) and modal analyses
- Dynamic system simulations
- Powertrain mounting strategies
- Body mounting concepts
- Suspension configurations
- Vehicle simulations
- Competitor benchmarking



LIGHTWEIGHT ICP® ACCELEROMETER

MODEL 352C22

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 0.7 to 13k Hz (±10 %)
- Weight: 0.017 oz (0.5 gm)
- Ground isolated



MINIATURE ICP® ACCELEROMETER

MODELS 352C65 & 352C68

- Sensitivity: 100 mV/g
- Measurement Range: ±50 g pk
- Frequency Range: 0.3 to 12k Hz (±10 %)
- Weight: 0.07 oz (2 gm)
- Ground isolation models available



GENERAL PURPOSE ICP® ACCELEROMETER

MODELS 352C03 & 352C04

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 0.3 to 15k Hz (±10 %)
- Weight: 0.20 oz (5.8 gm)
- Ground isolation, water resistant and TEDS models available



MINIATURE TRIAXIAL ICP® ACCELEROMETER

MODELS 356A01 & 356A03

- Sensitivity: 5 / 10 mV/g
- Measurement Range: ±1000 / ±500 g pk
- Frequency Range: 2 to 8k Hz (±1 dB)
- Small 0.25 (6.4 mm) adhesive mount cube
- Weight: 0.04 oz (1.0 gm)



TRIAxIAL ICP® ACCELEROMETER

MODEL 356A33

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 2 to 10k Hz (±5 %)
- Small 0.4 (10.2 mm) stud mountable cube
- Weight: 0.19 oz (5.3 gm)



HIGH FREQUENCY ICP® TRIAxIAL ACCELEROMETER

MODEL 356A19

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 0.6 to 15k Hz (±10 %)
- Weight: 0.14 oz (4 gm)
- TEDS IEEE 1451.4 enabled



HIGH SENSITIVITY ICP® TRIAxIAL ACCELEROMETER

MODEL 356A15

- Sensitivity: 100 mV/g
- Measurement Range: ±50 g pk
- Frequency Range: 1.4 to 6.5k Hz (±10 %)
- Electrical Connector: 1/4-28 4-Pin



HIGH SENSITIVITY ICP® TRIAxIAL ACCELEROMETER

MODEL 356B18


- Sensitivity: 1k mV/g
- Measurement Range: ±5 g pk
- Frequency Range: 0.3 to 5k Hz (±10 %)
- Electrical Connector: 1/4-28 4-Pin



GROUND ISOLATED TRIAXIAL HIGH SENSITIVITY ICP® ACCELEROMETER

MODEL 354C03

- Sensitivity: 100 mV/g
- Measurement Range: ±50 g pk
- Frequency Range: 0.5 to 4k Hz (±10 %)
- Electrical Connector: 1/4-28 4-Pin



VEHICLE & POWERTRAIN DEVELOPMENT

FILTERED, HIGH TEMPERATURE & THERMALLY STABLE SENSORS

Measuring NVH in powertrain and driveline applications presents a unique set of challenges. Whether internal combustion or electric drive systems, the influence of wide temperature ranges and signal saturation caused by metal-to-metal impacts on the quality of measurement can be significant.

The ability to mitigate the influence of these external environmental conditions while accurately capturing the desired data requires a thoughtful application of both transducer technologies and engineering foresight.

ELECTRICALLY FILTERED SENSORS

Environments with mechanical shock or significant high frequency vibration content necessitate specialized accelerometers designed with these demanding test conditions in mind. Mechanical shock events can excite the high frequency resonance of the piezoelectric crystal (PCB or others), saturating the signal and leading to clipping in the ICP® signal conditioned output. To combat the effects of the crystal resonance, PCB employs carefully selected low-pass filtering in select accelerometers.

This integrated pre-filtering minimizes the opportunity for erroneous frequency content to be generated and accepted as valid data, by suppressing the effects of the crystal resonance before it can influence the output signal. An additional purpose for filtering is to extend the usable high frequency range of the sensor by minimizing crystal resonance influence, resulting in an extended flat frequency response.

HIGH TEMPERATURE & THERMALLY STABLE SENSORS

Thermal influence on the performance of accelerometers is another aspect that needs to be considered when designing NVH testing plans. Both quartz and ceramic piezoelectric sensing elements have a measurable amount of thermally induced output, even at static condition. If ignored, this can potentially induce unaccounted for inaccuracies into the data being collected. To combat this, PCB has developed a specialized family of accelerometers that utilize UHT-12™ crystal technology which offers extremely stable sensitivity over a wide temperature range, far superior to quartz or ceramic.

In addition to improved accuracy over temperature, this family of accelerometers exhibit low noise, low base strain sensitivity and a wide operating frequency range. PCB's family of low temperature coefficient (LTC) sensors offers the capability to cover a wide variety of demanding applications. With filtering, temperature coefficients down to 0.005% / °F (0.009% / °C), and operating temperatures to 356 °F (180 °C), this family of hermetically sealed titanium accelerometers are ideal for evolving NVH testing challenges well into the future.

900°F
(482 °C)



VERY HIGH TEMPERATURE, SINGLE-ENDED CHARGE ACCELEROMETER

MODEL 357A63

- Sensitivity: 0.53 pC/g
- Measurement Range: ±5k g pk
- Frequency Range: 1 to 10k Hz (+10 %)
- Temperature Range: -65 to +900 °F (-54 to 482 °C)



UHT-12™ TRIAXIAL ICP® ACCELEROMETER

MODEL 339C31

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 1.5 to 11k Hz (±10 %)
- Temperature Range: -65 to 250°F (-54 to 121°C)

325°F
(162 °C)



MINIATURE THERMALLY STABLE ICP® ACCELEROMETER

MODEL 320C52 & 320C53

- Sensitivities: 10 / 1 mV/g
- Measurement Range: ±500 / ±5k g pk
- Frequency Range: 0.6 to 15k Hz / 0.6 to 10k Hz
- Temperature Range: -100 to +325 °F (-73 to 163 °C)
- Weight: .065 oz (1.85 gm)

325°F
(162 °C)



THERMALLY STABLE ICP® ACCELEROMETER

MODEL 320C20

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 1.5 to 10k Hz (±10 %)
- Temperature Range: -100 to +325 °F (-73 to 163 °C)

325°F
(162 °C)



FILTERED LTC TRIAXIAL ICP® ACCELEROMETER

MODELS TLD339A36 & TLD339A37

- Sensitivities: 10 / 100 mV/g
- Measurement Range: ±500 g pk / ±50 g pk
- Frequency Range: 1 to 8k / 0.2 to 7k Hz (±10 %)
- Temperature Ranges: -65 to 325 / 356°F (-54 to 163 / 180°C)

350°F
(177 °C)



MINIATURE HIGH TEMPERATURE CHARGE ACCELEROMETER

MODEL 357A08

- Sensitivity: 0.35 pC/g
- Measurement Range: ±1k g pk
- Frequency Range: 1 to 20k Hz (+10 %)
- Temperature Range: -100 to 350°F (-73 to 177°C)
- Weight: 0.006 oz (0.16 gm)



HIGH FREQUENCY ICP® ACCELEROMETER

MODEL 352A60

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 5 to 60k Hz (±3dB)
- Temperature Range: -65 to +250 °F (-54 to 121 °C)



HIGH FREQUENCY ICP® TRIAxIAL ACCELEROMETER

MODELS 356A24

- Sensitivity: 10 mV/g
- Measurement Range: ±500 g pk
- Frequency Range: 0.5 to 12k Hz (±10 %)
- Temperature Range: -65 to +250 °F (-54 to 121 °C)

490°F
(254 °C)



MINIATURE CHARGE TRIAXIAL ACCELEROMETER

MODEL 356A71

- Sensitivity: 10 pC/g
- Measurement Range: ±500 g pk
- Frequency Range: 1 to 7k Hz (+10 %)
- Temperature Range: -95 to +490 °F (-70 to 254 °C)
- Weight: 0.8 oz (22.7 gm)



NVH TESTING VC MEMS ACCELEROMETERS

PCB® series 3711F, 3713F, 3741F, and 3743F variable capacitance MEMS (VC MEMS) accelerometers are used to measure low frequency motion down to zero hertz. These accelerometers are used in NVH applications with low frequency and amplitude requirements, as well as road load data acquisition (RLDA), drivability, ride and handling, and vehicle performance testing. Each series includes a full scale measurement range from $\pm 2g$ to $\pm 200g$ and features low spectral noise with high resolution. The units feature capacitive, silicon MEMS sensing elements for uniform, repeatable performance and offer high frequency overload protection.



SINGLE-ENDED VC MEMS ACCELEROMETERS

SERIES 3711F & 3713F

- Sensitivities:
6.75 mV/g to 675 mV/g ($\pm 3\%$)
- Measurement Range:
 $\pm 2 g$ pk to $\pm 200 g$ pk
- Frequency Range:
from 0 Hz up to 2.5k Hz ($\pm 10\%$)
- Available with integral cable or multi-pin, threaded electrical connector
- Available in single-axis or triaxial configurations



DIFFERENTIAL OUPUT, SINGLE AXIS VC MEMS ACCELEROMETERS

SERIES 3741F

- Sensitivities:
13.5 mV/g to 1350 mV/g ($\pm 3\%$)
- Measurement Range:
 $\pm 2 g$ pk to $\pm 200 g$ pk
- Frequency Range:
from 0 Hz up to 2.5k Hz ($\pm 10\%$)
- Ground isolated, hard-anodized aluminum housing
- Integral, 4-conductor shielded cable



DIFFERENTIAL OUPUT, TRIAXIAL VC MEMS ACCELEROMETERS

SERIES 3743F

- Sensitivities:
13.5 mV/g to 1350 mV/g ($\pm 3\%$)
- Measurement Range:
 $\pm 2 g$ pk to $\pm 200 g$ pk
- Frequency Range:
from 0 Hz up to 2.5k Hz ($\pm 10\%$)
- Case isolated, hermetically sealed titanium housing
- 9-Pin threaded electrical connector

RIDE QUALITY ELECTRIC VEHICLE DEVELOPMENT

Hybrid and electric vehicles present unique NVH testing challenges due to vehicle complexity and potential for problems with electrical isolation. NVH issues related to the addition of new electrical devices, gear whine, and vehicle resonances increase the number of areas and components to be tested. PCB's broad line of accelerometers are engineered to meet these challenges with ground and case isolation. These accelerometers are ideal for use in strong electrical fields generated by electric and hybrid vehicle systems. Electrical isolation reduces noise in these fields and eliminates ground loops.



GROUND ISOLATED TEDS TRIAxIAL ACCELEROMETER

MODELS J356A43, J356A44, J356A45

- Sensitivities: 10 mV/g / 50 mV/g / 100 mV/g
- Measurement Range: ± 500 g pk / ± 100 g pk / ± 50 g pk
- Frequency Range: 0.4 to 10k Hz (± 10 %)
- TEDS Compliant



MINIATURE TRIAXIAL ICP® ACCELEROMETER

MODEL J356A03

- Sensitivity: 10 mV/g
- Measurement Range: ± 500 g pk
- Frequency Range: 2 to 8k Hz (± 5 %)
- Small 0.28 (7.1 mm) adhesive mount cube
- Weight: 0.04 oz (1 gm)



MINIATURE CERAMIC SHEAR ICP® ACCELEROMETER

MODEL 352A24

- Sensitivity: 100 mV/g
- Measurement Range: ± 50 g pk
- Frequency Range: 0.8 to 10k Hz (± 10 %)
- Weight: 0.03 oz (0.8 gm)



HIGH SENSITIVITY ICP® ACCELEROMETER

MODEL J352C33

- Sensitivity: 100 mV/g
- Measurement Range: ± 50 g pk
- Frequency Range: 0.3 to 15k Hz (± 10 %)
- Integral ground isolation base



CASE ISOLATED HIGH SENSITIVITY TRIAXIAL ICP® ACCELEROMETER

MODEL 354B04 & 354B05

- Sensitivity: 10 and 100 mV/g
- Measurement Range: ± 500 g pk / ± 50 g pk
- Frequency Range: 0.6 to 10k Hz (± 5 %)
- TEDS Compliant



INTRINSICALLY SAFE ACCELEROMETER

MODEL EX639A91

- Sensitivity: 100 mV/g
- Measurement Range: ± 50 g pk
- Frequency Range: 1.5 to 5.5k Hz (± 5 %)
- IP68-rated 4-Pin, M12 connector

NVH TESTING ACOUSTICS

Noise source measurements during the vehicle design process can present unique challenges. As electric vehicle design efforts overtake that of conventional vehicles, the demands for better resolution, lower noise floor and broader frequency response become more important to achieving a successful measurement.

PCB's line of acoustic measurement products includes condenser, prepolarized, externally polarized, array, probe, low-profile surface, water and dust resistant, high temperature and other special purpose microphones, designed to accommodate virtually any sound testing environment.

With a broad product offering, measurements such as buzz, squeak and rattle (BSR), noise path analysis/transfer path analysis (NPA/TPA), and pass-by noise are common applications where the rugged design and exceptional performance of PCB microphones can be regularly found. Challenging measurement environments such as under-hood and in wheel-well can easily be addressed with microphones specially designed for use in extreme temperatures, high humidity and dirty environments.

Prepolarized microphones have many advantages over externally polarized models. They use low power circuitry and do not require an external polarization voltage, making them especially useful in applications that require battery powered equipment. Adding to their ease of use, prepolarized microphone systems use common coaxial cables with BNC connectors and can be shared with other ICP® compatible products, including accelerometers, force sensors, and pressure sensors.

Portability and interchangeability with other sensors minimize test set-up time and reduce the cost per-channel. All PCB microphones come standard with transducer electronic data sheets (TEDS) for microphone identification.



1/2" PREPOLARIZED LOW NOISE MICROPHONE SYSTEM

MODEL 378A04

- Sensitivity: 450 mV/Pa
- Frequency Range: 5 to 16k Hz (± 2 dB)
- Inherent Noise: 5.5 dB(A) re 20 μ Pa
- Dynamic Range: (3% Distortion Limit) >80 dB re 20 μ Pa
- Noise Floor: 5.5 dB(A)
- TEDS Compliant



1/2" PREPOLARIZED FREE-FIELD CONDENSER MICROPHONE

MODEL 378B02


- Sensitivity: 50 mV/Pa
- Frequency Range: 3.75 Hz to 20 kHz (± 2 dB)
- Inherent Noise: 15.5 dB(A) re 20 μ Pa
- Dynamic Range: 137 dB re 20 μ Pa
- TEDS Compliant



1/2" PREPOLARIZED RANDOM INCIDENCE CONDENSER MICROPHONE

MODEL 378C20

- Sensitivity: 50 mV/Pa
- Frequency Range: 3.75 Hz to 20 kHz (± 2 dB)
- Inherent Noise: 16 dB(A) re 20 μ Pa
- Dynamic Range: 137 dB re 20 μ Pa
- TEDS Compliant



1472°F
(800°C)



HIGH TEMPERATURE PROBE MICROPHONE

MODEL 377B26

- Sensitivity: 2.15 mV/Pa
- Frequency Range: 2 to 20k Hz (+2.2/-4.9dB)
- Inherent Noise: 44 dB(A) re 20 μPa
- Dynamic Range: 165 dB re 20 μPa
- Temperature Range: -40 to +1472° F (-40 to +800°C)



ICP® ARRAY MICROPHONE

MODELS 130F20, 130F21, 130F22

- Sensitivity: 45 mV/Pa
- Frequency Range: 10 to 16k Hz (±3dB)
- Inherent Noise: 29 dB re 20 μPa (Linear)
- Dynamic Range: 122 dB re 20 μPa
- TEDS Compliant



ICP® LOW PROFILE PRESSURE MICROPHONE

MODEL 130B40

- Sensitivity: 8.5 mV/Pa
- Frequency Range: 20 to 10k Hz (±3dB)
- Inherent Noise: <32 dB(A) re 20 μPa
- Dynamic Range: 150 dB re 20 μPa
- TEDS Compliant



ICP® WATER RESISTANT ARRAY MICROPHONE

MODEL 130A24

- Sensitivity: 10 mV/Pa
- Frequency Range: 20 to 16k Hz (±3dB)
- Inherent Noise: <30 dB(A) re 20 μPa
- Dynamic Range: 143 dB re 20 μPa
- TEDS Compliant



1/4" LOW NOISE ICP® PREPOLARIZED MICROPHONE SYSTEM

MODEL 378A08

- Sensitivity: 50 mV/Pa
- Frequency Range: 12 to 20k Hz (±2 dB)
- Inherent Noise: ≤25 dB(A) re 20 μPa
- Dynamic Range: 123 dB re 20 μPa
- TEDS Compliant



1/4" PREPOLARIZED PRESSURE MICROPHONE

MODEL 378C10

- Sensitivity: 1 mV/Pa
- Frequency Range: 5 to 70k Hz (±2dB)
- Dynamic Range: 173 dB re 20 μPa
- Inherent Noise: 50 dB(A) re 20 μPa
- TEDS Compliant

RECOMMENDED TESTING SOLUTIONS

SHAKER KITS FOR VIBRATION TESTING

The Modal Shop's exciter family provides solutions for applications ranging from experimental modal analysis to general vibration testing of small components and sub-assemblies. The broad range of shakers includes small-sized 2 lbf (10 N) up to 500 lbf (2,224 N).

Available designs include the revolutionary SmartShaker™ with integrated power amplifier providing a high degree of flexibility when testing and Modal Shakers designed with a through-hole armature to simplify a common testing challenge: stinger setup and alignment. The mini inertial shaker is well-suited for structural testing in small, confined locations and dual purpose platform shakers are ideal for component testing.



IMPEDANCE HEAD

MODEL TLD288D01

- ICP® impedance head (force/acceleration) for driving point measurements
- Force: 100 mV/lbf, ± 50 lbf
- Accel: 100 mV/g, ± 50 g
- Available with TEDS functionality



DIGITAL ICP® SIGNAL CONDITIONER

MODEL 485B39

- Powers ICP® sensors while digitizing signals
- Pocket-sized, dual channel with standard USB digital output
- Plug & Play signal conditioning offers quick setup and simple usability with no driver installation needed



AIRRIDE® MOUNT

MODEL 8032S

- Provides extremely low mounting frequencies for large rigid body test structures
- Eliminates multiple mounting frequencies, as AirRide® natural frequency does not shift significantly with changes in load



DIGIDUCER® USB DIGITAL ACCELEROMETER

MODEL 333D01

- Piezoelectric ruggedness and dynamic range
- Eliminates need for data acquisition
- Flat response up to 8 kHz
- Plug & Play – record vibration data via laptop or tablet



LATERAL EXCITATION STAND

MODEL 2050A

- Combining lateral and vertical excitation distributes input energy and helps excite uncoupled lateral modes
- Provides versatility to adapt a modal shaker for horizontal input
- Ensures proper alignment with coarse and fine vertical adjustment



ICP® LASER TACHOMETERS

MODEL LT2


- Operates with standard ICP® signal conditioning; simplifies cabling
- One pulse/rev eliminates need to oversample all channels for a high frequency tach
- Offers continuous laser for jitter-free operation

PRECISION SENSOR CALIBRATION WORKSTATION


The Precision Sensor Calibration Workstation Model 9155 is a turnkey solution that provides all the necessary components out of the box. Principal components include a Windows® PC controller, software, printer, and 24-bit data acquisition card with software.

System options allow custom configuration of the modular system with a variety of calibration-grade exciter systems and signal conditioning. The Model 9155 can calibrate a wide range of accelerometers (including ICP®, charge, MEMS, and piezoresistive), microphones (including array, phantom power, externally polarized, and prepolarized), and dynamic pressure sensors.

To learn more about how a 9155 system can meet your specific needs, visit www.modalshop.com/configure for a custom calibration configuration guide or contact The Modal Shop's Calibration Team.



RECOMMENDED SENSOR ACCESSORIES



ADHESIVE MOUNTING BASE
MODEL 080A



TRIAXIAL MOUNTING ADAPTER
MODEL 080B16



ADHESIVE
MODEL 080A90



MOUNTING CLIP
MODEL 080A237



PETRO WAX
MODEL 080A109



REMOVAL TOOL
MODEL 039A08



4-CONDUCTOR, SHIELDED, FEP CABLE
MODEL 034WXX

- Used with triaxial ICP® accelerometers
- 4 conductor, shielded, FEP jacket
- IP68 Rated 1/4-28, 4-socket plug to 3 BNC plugs



4-CONDUCTOR, SHIELDED, POLYURETHANE CABLE
MODEL 078WXX

- Used with triaxial ICP® accelerometers
- 4 conductor, shielded, flexible polyurethane jacket
- IP68 Rated 1/4-28, 4-socket plug to 3 BNC plugs



NF CABLE
4-CONDUCTOR TERMINATION

- Connector Style: Triple Splice
- Connector Style: BNC
- Connection Type: Plug (male pin)
- Temperature Range: -40 to +176 °F (-40 to +80 °C)
- Grounded shield

RECOMMENDED ACOUSTIC ACCESSORIES



ADAPTOR
MODEL ADP043



NOSE CONE
MODEL 079B21



WINDSCREEN
MODEL 079A06
MODEL 079A07



PREAMPLIFIER HOLDER
MODEL 079A11



SWIVEL HEAD ADAPTOR
MODEL 079B23



MICROPHONE STAND
MODEL 079A15



 **PCB PIEZOTRONICS**
AN AMPHENOL COMPANY

3425 Walden Avenue, Depew, NY 14043 USA

pcb.com | info@pcb.com | 800 828 8840 | +1 716 684 0001

© 2024 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevco is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevco), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.

AUTO-NVH-0924