Model Number	CABLE CONNECTOR				Revision: NR ECN #:
Performance Connector Style	<u>ENGLISH</u> Double Splice BNC	<u>SI</u> Double Splice BNC	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard mode except where noted below. More than one option may be used.		
Connection Type	Plug (male pin)	Plug (male pin)			
Coupling Method	Bayonet	Bayonet			
Strain Relief	Molded Boot	Molded Boot			
Environmental					
Temperature Range Physical	-40 to +176 °F	-40 to +80 °C			
Electrical Connections	Acceleration	Acceleration	Entered: Lot Enginee May S	ales: M n Approved: E	0
	Temperature	Temperature	Entered. Congineety (4)	ales: / / / Approved: E	Spec Number
ROHS Compliant	No	No	Date: 8-25-09 Date: 8-17-09 D	12to: \$ 1 C . 10 Data: 6 700	υ ς 43843
Size (Length)	12 in	30.5 cm	Date. 8, 23, 0-1 Date. 0. (1.0-1 D	ale. 0 18 05 Dale. 8-27	27 43043
All specifications are at room temperatu In the interest of constant product impro	ure unless otherwise specified. Overnent, we reserve the right to change s	specifications without notice.	IMISENSORS	IMI Sensors 3425 Walden Depew, NY 14043 UNITED STATES	



Phone: 800-959-4464 Fax: 716-684-3823

E-Mail: imi@pcb.com Web site: http://www.imi-sensors.com