


Model Number SB	<b>CABLE CONNECTOR</b>			Revision: NR ECN #: 50560
<b>Performance</b> Connector Style Connection Type Connection Type Coupling Method <b>Environmental</b> Temperature Range Radiation Exposure Limit(Integrated Neutron Flux) Radiation Exposure Limit(Integrated Gamma Flux) <b>Physical</b> Size (OD x Length) Weight Sealing	<b>ENGLISH</b> Multi-conductor 2-pin Plug (male pin) Threaded -65 to 900 °F 1 E10 N/cm <sup>2</sup> 1 E8 rad 0.44 in x 1.5 in 0.62 oz Hermetic	<b>SI</b> Multi-conductor 2-pin Plug (male pin) Threaded -54 to 482 °C 1 E10 N/cm <sup>2</sup> 1 E8 rad 11.2 mm x 38.1 mm 17.6 gm Hermetic		<b>OPTIONAL VERSIONS</b> Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
				<b>NOTES:</b> [1]When used with 013 cable
				Entered: LK    Engineer: EB    Sales: MC    Approved: RPF    Spec Number: Date: 04/03/2020    Date: 04/03/2020    Date: 04/03/2020    Date: 04/03/2020    73012
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				 <b>Phone: 716-684-0001</b> <b>Fax: 716-684-0987</b> <b>E-Mail: info@pcb.com</b> 3425 Walden Avenue, Depew, NY 14043