Model Number 231B	CHARGE OUTPUT FORCE SENSOR							ision: F I #: 40706
Performance				OPTIONAL VERSIONS				
Sensitivity(± 15 %) Measurement Range(Compression Measurement Range(Tension) Maximum Static Force(Compression	≤ 1000 lb	4047 pC/kN ≤ 22.24 kN ≤ 4.448 kN 24.47 kN		Optional versions have identical specifications and accessories as listed for the except where noted below. More than one option may be used. J - Ground Isolated				
Maximum Static Force(Tension) Upper Frequency Limit	1200 lb 15 kHz	5.338 kN 15 kHz	[2][3]	M - Metric Mount				
Non-Linearity Environmental	≤ 1 % FS	≤ 1 % FS	[4]	Mounting Thread		No English E	No English Equivalent M6 x 0.75	
Temperature Range Temperature Coefficient of Sensitiv	-100 to +400 °F ity ≤ 0.01 %/°F	-73 to +204 °C ≤ 0.018 %/°C		P - Positive Output Polarity				
Electrical Capacitance Insulation Resistance	≥ 12 pF ≥ 10 ¹² Ohm	≥ 12 pF ≥ 10 ¹² Ohm	[1]	W - Water Resistant Cable Electrical Connection Position		Side		Side
Physical								
Stiffness Size (Diameter x Height) Weight Housing Material Sealing Electrical Connector Electrical Connector	2 lb/µin 0.65 in x 1.25 in 1.1 oz Stainless Steel Hermetic 10-32 Coaxial Jack Side	0.35 kN/µm 16.51 mm x 31.75 mm 31 gm Stainless Steel Hermetic 10-32 Coaxial Jack Side	[1]	 NOTES: [1] Typical. [2] Estimated using rigid body dynamics calculations. [3] Low frequency response and system noise dependent on choice of external signal conditioning electronics. [4] Zero-based, least-squares, straight line method. 				
Mounting Thread	1/4-28 Female	No Metric Equivalent		Entered: AP	Engineer: JDK	Sales: KWW	Approved: APB	Spec Number:
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.			Э.	Date: 3/18/2013	Date: 3/18/2013	Date: 3/18/2013	Date: 3/18/2013	1238
ICP [®] is a registered trademark of F	CB Group, Inc.						Dhama: 71	6 684 0004
	PCB PIEZOTRONICSPhone: 716-684-0003425 Walden Avenue, Depew, NY 14043Fax: 716-684-0987E-Mail: info@pcb.cd						84-0987	