| Model Number 121A45 | | | | | | | | evision: C CN #: 54975 |
|---|----------------------------------|-------------------------------|---------|---------------------|--|----------------------|---|---------------------------|
| Performance | ENGLISH | SI | | | 0 | PTIONAL VERSI | ONS | |
| Measurement Range(for ±5V output) | 500 psi | 3,447 kPa | | Optional versions | have identical specifi | cations and accessor | ies as listed for the st option may be used. | andard model exe |
| Sensitivity(± 15 %) | 10 mV/psi | 1.45 mV/kPa | | | where noted be | low. More than one o | option may be used. | |
| Maximum Pressure | 8,000 psi | 55,158 kPa | | | | | | |
| Resolution | 3 mpsi | 0.02 kPa | [1] | | | | | |
| Resonant Frequency | ≥ 60 kHz | ≥ 60 kHz | 1.11 | | | | | |
| Rise Time(Reflected) | | ≥ 00 kH2 ≤ 4 µ sec | | | | | | |
| Low Frequency Response(- 5 %) | ≤ 4 µ sec 0.5 Hz | ≤ 4 µ sec 0.5 Hz | | | | | | |
| Non-Linearity | ≤ 2.0 % FS | ≤ 2.0 % FS | [2] | | | | | |
| Environmental | ≤ 2.0 % F3 | ≤ 2.0 % F3 | [2] | | | | | |
| Acceleration Sensitivity | 0.025 psi/g | 0.018 kPa/(m/s ²) | [1] | | | | | |
| Temperature Range(Operating) | -65 to +250 °F | -54 to +121 °C | [1] | | | | | |
| Hazardous Area Approval | See Manual | See Manual | | | | | | |
| Electrical | See Maridai | See Manual | | | | | | |
| Output Polarity(Positive Pressure) | Positive | Positive | | | | | | |
| Discharge Time Constant(at room temp) | ≥ 1.0 sec | ≥ 1.0 sec | | | | | | |
| | | | | | | | | |
| Excitation Voltage Constant Current Excitation | 22 to 28 VDC 2 to 20 mA | 22 to 28 VDC 2 to 20 mA | | | | | | |
| | 2 to 20 mA < 100 Ohm | | | | | | | |
| Output Impedance | < 100 Onm 8 to 14 VDC | < 100 Ohm 8 to 14 VDC | | | | | | |
| Dutput Bias Voltage | | | | | | | | |
| Electrical Isolation | ≥ 10 ⁸ Ohm | ≥ 10 ⁸ Ohm | | | | | | |
| Physical | - | | | | | | | |
| Sensing Geometry | Compression | Compression | | | | | | |
| Sensing Element | Quartz | Quartz | | | | | | |
| Housing Material | 316L Stainless Steel | 316L Stainless Steel | | | | | | |
| Diaphragm | 316L Stainless Steel | 316L Stainless Steel | | | | | | |
| Sealing | Welded Hermetic | Welded Hermetic | | | | | | |
| Electrical Connector Weight | 2-Pin MIL-C-5015 2.7 oz | 2-Pin MIL-C-5015 75.6 gm | | | | | | |
| | | | | | ast-squares, straight ration of Conforman | | | |
| | | | | iviodel PCS- i Cali | oration of dynamic pr | essure sensors at 10 | 0% full scale, max 15 | kpsrrange. |
| (| | | | Entered: ND | Engineer: AJA | Sales: RWM | Approved: RPF | Spec Number: |
| | | | | Date: 07/16/2024 | Date: 07/16/2024 | Date: 07/16/2024 | Date: 07/16/2024 | 38074 |
| CE UK Ispecifications are at room temperature of In the interest of constant product improver ICP [®] is a registered trademark of PCB Piezo | nent, we reserve the right to ch | nange specifications without | notice. | | PIEZOTRO AN AMPHENOL hue, Depew, NY 1404 | COMPANY Fax: 71 | 716-684-0001 6-684-0987 info@pcb.com | - |