

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Number of Conductors	24	24	
Cable Style	Multi Conductor - Shielded	Multi Conductor - Shielded	
Cable Configuration	Twisted Pair	Twisted Pair	
Environmental			
Temperature Range	-40 to +221 °F	-40 to +105 °C	
Physical			
Cable Jacket Diameter	0.61 in	15.5 mm	[1]
Cable Jacket Material	PVC	PVC	
Cable Jacket Color	Black	Black	
Conductor Style	Stranded - 7 Strands 28 AWG	Stranded - 7 Strands 28 AWG	
Conductor Material	Tin Plated Copper	Tin Plated Copper	
Conductor Diameter(20 AWG)	0.038 in	0.97 mm	[1]
Insulation Material Over Conductor(s)	PVC	PVC	
Shield Type Over Bundle	Foil	Foil	
Shield Material Over Bundle	Aluminum / Mylar	Aluminum / Mylar	
Drain Wire Material	Tin Plated Copper	Tin Plated Copper	
Drain Wire Diameter(22 AWG)	0.030 in	0.76 mm	[1]
Bend Radius(minimum)	6 in	152.4 mm	
Weight	3.0 oz/ft	276 gm/m	[1]
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p><i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p> <p>ICP® is a registered trademark of PCB Group, Inc.</p>			

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
[1] Typical.

Entered: <i>JH</i>	Engineer: <i>mm</i>	Sales: <i>JG</i>	Approved: <i>EB</i>	Spec Number:
Date: <i>3-9-09</i>	Date: <i>3-5-09</i>	Date: <i>3-5-09</i>	Date: <i>3-9-09</i>	31751



IMI SENSORS
A PCB PIEZOTRONICS DIV.

IMI Sensors
3425 Walden
Depew, NY 14043
UNITED STATES
Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com
Web site: <http://www.imi-sensors.com>