


Model Number 052BR010AC	POLYURETHANE JACKETED CABLE ASSEMBLY		Revision NR ECN #:						
Performance Cable Style Number of Conductors Connector Model (sensor side) Connector Style (sensor side) Connection Type (sensor side) Coupling Method (sensor side) Connector Style (termination) Environmental Temperature Range Electrical Capacitance Physical Cable Jacket Diameter Cable Jacket Material Cable Jacket Color Conductor Style Conductor Material Conductor Diameter (20 AWG) Shield Type Over Bundle Shield Material Over Bundle Bend Radius (minimum) Weight	ENGLISH Multi Conductor - Shielded 2 molded composite MIL-C-5015 2-pin Threaded BNC -58 to 250 °F 36 pF/ft 0.25 in Polyurethane Black Stranded - 19 strands 32 AWG Tin Plated Copper 0.04 in Braid: 90% Minimum Coverage Tin Plated Copper 2.5 in 0.67 oz/ft	SI Multi Conductor - Shielded 2 molded composite MIL-C-5015 2-pin Threaded BNC -50 to 121 °C 118 pF/m 6.35 mm Polyurethane Black Stranded - 19 strands 32 AWG Tin Plated Copper 1.02 mm Braid: 90% Minimum Coverage Tin Plated Copper 63.5 mm 61.85 gm/m	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)						
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p> <p>ICP® is a registered trademark of PCB group, Inc.</p>									
Entered: ECB Date: 01/30/2010		Engineer: MJN Date: 01/30/2010		Sales: MRS Date: 01/30/2010		Approved: EGY Date: 01/30/2010		Spec Number: N/A	
					3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com Web site: www.pcb.com				