


Model Number <b>488A03</b>	<b>POWER SUPPLY</b>				Revision: C ECN #: 39050
<b>Electrical</b>	<b>ENGLISH</b>	<b>SI</b>			<b>OPTIONAL VERSIONS</b>
DC Power(Output) (Output)	27 VDC 20 mA	27 VDC 20 mA			Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
AC Power(60 Hz)	100 to 125 VAC	100 to 125 VAC	[1][2]		
(60 Hz)	0.125 amps	0.125 amps	[1]		
(50 Hz)	200 to 250 VAC	200 to 250 VAC	[1][2]		
(50 Hz)	0.125 amps	0.125 amps	[1]		
AC Ripple(Peak to Peak)	<1.5 mV	<1.5 mV			
<b>Physical</b>					<b>NOTES:</b>
Electrical Connector(AC Power Input)	IEC 320	IEC 320			[1] AC input voltage selectable by switch on the side of unit (115 VAC or 230 VAC).
(Output DC)	750 Switchcraft	750 Switchcraft			[2] F488A03 provided with switch set to 230 VAC.
Size (Height x Width x Depth)	4.0 in x 2.9 in x 1.5 in	101.6 mm x 73.7 mm x 38.1 mm			
Weight	0.8 lb	0.36 Kg			
<i>All specifications are at room temperature unless otherwise specified.</i>					
<i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>					
ICP® is a registered trademark of PCB Group, Inc.					
<b>SUPPLIED ACCESSORIES:</b>					
Model 017AXX Power Cord (1)					
Entered: <i>Lu</i>	Engineer: <i>KL</i>	Sales: <i>JM</i>	Approved: <i>BM</i>	Spec Number:	
Date: <i>4-23-12</i>	Date: <i>4-11-12</i>	Date: <i>4-13-12</i>	Date: <i>4-17-12</i>	1827	
				Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	
3425 Walden Avenue, Depew, NY 14043					