Model Number **488B07**

BATTERY PACK FOR 482A21 & 482A22

Revision: A

ECN #: 11487

ELECTRICAL

Output Voltage (nominal)

9V x 4 Duracell MN1604 (or equivalent) Alkaline Battery

Typical Battery Life:

482A21 @ 4 mA

482A22 @ 4 mA/ch

+ volts mA/hrs

hrs

hrs

36 565

125

32

[1]

PHYSICAL

Case
Output Cable (1 ft long)

Size: H x W x D (case only)

Weight (with batteries installed)

CE/UL (flammability)

plug/DIN

ability) 94V-0 5-Pin

in [mm] lb [kg] 5-Pin 1.775 x 2.61 x 4.89 [45,1 x 66,3 x 124,2]

0.83 [0,38]

NOTES:

[1] Battery life in hours (minimum) =

500 mA - hours

ICP mA x number of channels used (typical)

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Piezotronics, Inc.

PCB PIEZOTRONICS

	2		
Drawn 🍠	HUS IT	FEB17,00	Spec No.
Engineer 4	POA	2/17/00	12766
Sales	EJR	2/17/00	
Approved	CAIL	2/17/00	Sheet 1 of 1