

	<u>ENGLISH</u>	<u>SI</u>
Environmental		
Temperature Range(Operating)	32 to 104 °F	0 to 40 °C
Humidity Range(Non-Condensing)	0 to 95 %	0 to 95 %
Electrical		
Output Voltage	32 - 38 VDC	32 - 38 VDC
Output Current	0.54 amps	0.54 amps
AC Power(50 to 60 Hz)	100 to 240 VAC	100 to 240 VAC
(50 to 60 Hz)	0.6 amps	0.6 amps
AC Ripple(Peak to Peak)	<350 mV	<350 mV
Physical		
Electrical Connector(AC Power Input)	IEC 320	IEC 320
(Output DC)	6-pin mini DIN (male)	6-pin mini DIN (male)
Size (Height x Width x Depth)	1.3 in x 2.13 in x 3.76 in	33 mm x 54.1 mm x 95.5 mm
Weight	1.25 lb	0.57 kg

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
[1] See PCB Declaration of Conformance PS024 for details.

SUPPLIED ACCESSORIES:
Model 017AXX Power Cord (1)

Entered: <i>JH</i>	Engineer: <i>PH</i>	Sales: <i>Jm</i>	Approved: <i>EB</i>	Spec Number:
Date: <i>3-24-10</i>	Date: <i>3-18-10</i>	Date: <i>3-18-10</i>	Date: <i>3-19-10</i>	44751



*All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.

PCB PIEZOTRONICS
ELECTRONICS DIVISION

3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: electronics@pcb.com