Model Number LU	CABLE CONNECTOR							ision: NR I #:
Performance Connector Style	ENGLISH Circular Breakaway	SI Circular Breakaway		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.				
Coupling Method Strain Relief	3-pin Plug (male pin) Snap-on Potted	3-pin Plug (male pin) Snap-on Potted						
Environmental Temperature Range Electrical	-40 to +176 °F	-40 to +80 °C		NOTES:				
Insulation Resistance Physical	10 Gohm	10 Gohm		[1] Typical.				
ROHS Compliant	No	No		-	24.0			ř
Housing Material	Plastic	Plastic		Entered: 16	Engineer 77	Sales: MRS	Approved: 3	Spec Number:
Size (OD x Length)	0.75 in x 2.2 in	19 mm x 57 mm		212200	2 22 0	700 0	2 2 22 6	1000
Weight	0.36 oz	10.1 gm	[1]	Date: 7-29-09	Date: 1-000	Date: FUT-09	Date: 7-27-09	43637
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				IMI Sensors 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com Web site: http://www.imi-sensors.com				