Model Number NP		CABLE CONNECTOR							rision: NR N#:
Performance Connector Style Strain Relief Physical		ENGLISH Pigtail Heat Shrink	SI Pigtail Heat Shrink	[1]	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.				
Electrical Connections(Red) (Black) (Yellow) (Blue) (Orange) (Brown) (Green) (White)		Ground	Pos (+) Power Ground X axis Pos (+) Output X Axis Neg (-) Output Y axis Pos (+) Output Y axis Neg (-) Output Z axis Pos (+) Output Z axis Neg (-) Output		NOTES: [1] Labeled for use with Series 3503 triax shock accelerometer.				
ROHS Compliant	(Solid Wire)	Shield N o	Shield No		Entered: LLH	Engineer: NJL	Sales: JJM	Approved: APB	Spec Number:
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.					Date: 4/1/2010	Date: 3/30/2010	Date: 3/30/2010	Date: 3/30/2010	45893
ICP [®] is a registered	i trademark of PCB Grou	up, Inc.	>		l .	PIEZOTA ELECTRONIC: enue, Depew, NY 14	BONISION	Phone: 716-684 Fax: 716-684-09 E-Mail: electro	