

| | <u>ENGLISH</u> | <u>SI</u> | |
|---|-----------------------------|-----------------------------|--------|
| Performance | | | |
| Measurement Range(Full Scale Capacity) | 100 lbf-in | 11.3 Nm | |
| Sensitivity(output at rated capacity) | 2.0 mV/V | 2.0 mV/V | [5] |
| Non-Linearity | ≤ 0.25 % FS | ≤ 0.25 % FS | [2] |
| Hysteresis | ≤ 0.25 % FS | ≤ 0.25 % FS | [2] |
| Non-Repeatability | ≤ 0.05 % FS | ≤ 0.05 % FS | [2] |
| Interchangeability | ≤ 0.30 % FS | ≤ 0.30 % FS | [6][2] |
| Environmental | | | |
| Overload Limit | 150 lbf-in | 16.9 Nm | |
| Temperature Range(Operating) | 0 to +200 °F | -18 to +93 °C | |
| Temperature Range(Compensated) | +70 to +150 °F | +21 to +66 °C | |
| Temperature Effect on Output(Maximum) | ± 0.002 %Reading/°F | ± 0.0018 %Reading/°C | [4] |
| Temperature Effect on Zero Balance(Maximum) | ± 0.002 %FS/°F | ± 0.0018 %FS/°C | [4] |
| Electrical | | | |
| Bridge Resistance | 350 Ohm | 350 Ohm | |
| Excitation Voltage | 10 VDC | 10 VDC | [1] |
| Insulation Resistance | ≥ 5 GOhm | ≥ 5 GOhm | |
| Zero Balance | ≤ 2 % FS | ≤ 2 % FS | [2] |
| Shunt Calibration | ≤ 0.25 % FS | ≤ 0.25 % FS | [3][2] |
| Physical | | | |
| Size (Shaft Length x Housing Length x Housing Height) | 2.37 in x 1.69 in x 1.30 in | 60.2 mm x 42.9 mm x 33.0 mm | [7] |
| Weight | .75 lb | 340 gm | |
| Mounting | 1/4 inch Sq Drive | 6.35 mm Sq Drive | |
| Sensing Element | Strain Gage | Strain Gage | |
| Housing Material | Aluminum | Aluminum | |
| Shaft Material | Steel | Steel | |
| Electrical Connector | PT02H-8-4P | PT02H-8-4P | |
| Maximum Speed | 5000 RPM | 5000 RPM | |

*All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
 [2] FS - Full Scale.
 [3] Matched with 43.575 kOhm Precision Resistor.
 [4] Over compensated temperature range.
 [5] Matched to ±0.25% F.S.
 [6] Matched for mV/V and shunt calibration.
 [7] See Outline Drawing 65559 for Complete Dimensions

SUPPLIED ACCESSORIES:
Model 7122R-04352A PRECISION CAL RESISTOR 43.575 kOhm

OPTIONAL ACCESSORIES:
 Model 080920-01000 Model 920 Portable Digital Peak Meter for torque, torque-angle or load measurement; Click-Wrench calc feature, w/battery charger, instruction manual & shoulder strap
 Model 080962-01000 MODEL 962 DATA RECORDER
 Model 097000-34149 INTERCONNECT CABLE
 Model 4242R-000600 MATING CONNECTOR PT06A-8-4S

| | | | | |
|-----------------|-----------------|-----------------|-----------------|--------------|
| Entered: LK | Engineer: PE | Sales: DM | Approved: JSD | Spec Number: |
| Date: 1/20/2017 | Date: 1/20/2017 | Date: 1/20/2017 | Date: 1/20/2017 | 65560 |

PCB Load & Torque
 24350 Indoplex Circle
 Farmington Hills, MI 48335
 UNITED STATES
 Phone: 866-684-7107
 Fax: 716-684-0987
 E-Mail: ltinfo@pcbloadtorque.com
 Web site: <http://www.pcbloadtorque.com>



PCB LOAD & TORQUE
A PCB PIEZOTRONICS DIV.